



Design and Fabrication of Excavator Assist with wheel

V.Rajesh^{1*}, Mr. Savarinathan K², Sanjana S³, Ambika⁴, Abhilipsa Nayak, Harini A⁵

¹ Assistant Professor, Department of Mechanical Engineering, Sri Sairam College of Engineering, VTU University

^{2,3,4,5} II Year, Department of Mechanical Engineering, Sri Sairam College of Engineering, VTU University

ABSTRACT

Ordinarily all the excavators are appended with either haggles dependent on their motivation of comprehending their necessities. The wheeled excavators are made for the development field which the prerequisites not exactly the followed excavator so these wheeled excavators are can be moved all alone as they are helped with wheels. The followed excavator is utilized with the end goal of hard core one. The followed excavators are shipped to one spot to another with the assistance of the hard core trucks. They have to stack the excavator on the truck and they have to ship it to the necessary spot and afterward it is should have been emptied from the truck and the connections are to be fitted alongside the excavators as per the need of the prerequisites. Consequently the extra truck compensation is to be paid to the truck Venders. Our undertaking assists with defeating the wages and the truck transportation our task is applied here. Our undertaking is to help the excavator with the extra haggles it tends to be lifted up when it isn't fundamental. For that we utilize the fundamental pressure driven line which controls the water driven engine to push the extra wheels. So it will be a productive one. The extra wheels are appended with the pressure driven lifting framework so it tends to be effortlessly lifted here and there when it is required.

Keywords: Hydraulic system, Hydraulic motor, Three-way valve, dead axle, DC Motor.

1 Introduction

Our project is to assist the excavator with the wheels for reducing the working wages of the excavator. Normally the excavators are not driven in the road surface as they will damage the road by the tracks. Ordinarily they are run by the tracks with the help of the hydraulic motors. So accordingly the excavators will not be transported as such the other hard core vehicles. The hard core trucks are used to transport the transport the excavators from one place to another place. The hard core truck wages are normally very high when compared to the normal trucks. The hard core tucks are used to transfer the excavator from one place to the other. So for that the transportation fee or fair is collected as per the hard core truck facilities. The excavator is to be lifted in the hard core truck and it should be placed in the correct placement as per the placement facilities. Then the truck is moved to the required place to deliver the excavator, then the excavator is unloaded from the truck and the required attachments are fitted in the excavator for the required work. The time consumption to load and unload the excavator is also calculated and distance travelling allowance is also added with the transportation cost. To overcome this extra wages and the time consumption that is done to unload and load the truck



our project is implemented in the excavator. The excavator is fitted with the hydraulic system as like the supporting leg in the back hook loader and then the dead axle is fitted along with the hydraulic system. Then the wheels are powered with the hydraulic motor and the hydraulic motor is constructed with the dead axle. Normally the excavator runs through the hydraulic motor so we also use the same hydraulic motor for the movement. The three-way valve is used to change the direction of the connection. Now the excavator can move in the roads without any additional trucks and its wages.

2 Recent Works

EUGENIUSZ et al [2010] inspected the disappointment brought about by cracked shaft of the can wheel. To investigate the disappointment discrete model has been created and utilizing FEM method examination has been done. At the broke area Macroscopic and infinitesimal picture has been taken dissect the tiny qualities so such disappointment of shaft can be forestalled in future

JOVANCIC et al [2011] analyze Load-Bearing limit of container wheel excavator and found that the power applied during exhuming activity are required to discover these powers for better structure of hardware, excavator parts and for direction arranging.

MIODRAG et al [2011] inspected the disappointment of can wheel brought about by remaining worries in welded joints utilizing FEM approach. The outcomes are contrasted and the numerical-exploratory outcome and uncovered that the mix of working (dynamic) and lingering (static) stress can be over the breaking point lines of changed Goodman's.

BABU et al [2014] advanced the excavator container utilizing limited component strategy. They create and basin for PC-09 and Zaxis-8-1 utilizing strong works and imported in ANSYS for transient investigation. They adjusted a few parameters and proposed an ideal plan.

R M DHAWALE et al are intended for excavating rocks and soils. It consists of four link members: the bucket, the stick, the boom and the revolving super structure. Thus it is very much necessary for the designers to provide not only a equipment of maximum reliability but also of minimum weight and cost, keeping design safe under all loading conditions.

[Babu] et al [2014] optimized the excavator bucket using finite element method. They develop and bucket for PC-09 and Zaxis-8-1 using solid works and imported in ANSYS for transient analysis. They modified some parameters and proposed an optimum design.

KALPAK et al [2015] The Excavator bucket tooth have to bear heavy loads of materials like soil, rock and subjected to abrasion wear due to the abrasive nature of soil particles. Its tooth got damaged due to abrasive wear and impact load. This paper deals with review of Excavators bucket tooth analysis to find out its actual failure.

J. KOIVO et al [1994], presented the kinematics of specific construction machines as excavators (backhoes and loaders). A systematic procedure is presented to assign Cartesian coordinate frames for the links (joints) of an excavator. If the lengths of the actuators or the joint variable angles are given, the position and orientation (pose) of the bucket are determined by the forward kinematic equations. If the position and orientation of the bucket are specified,



the joint variable angles corresponding to this bucket pose and the lengths of the actuators are calculated from the backward (inverse) kinematic equations. the corresponding velocity relations are derived for the hydraulically driven excavator (backhoe and loader). The kinematic equations presented establish the foundation for automatic computer control of this type of construction machine

3 Proposed Work Explanation

3.1 Working methodology

- The hydraulic cylinder is used to lift the additional wheel setup and firmly hold it until it is disengaged.
- The dead axle is used to attach the hydraulic motor with it for the transmission purpose.
- The valve is used to transfer the main hydraulic power to the additional wheels
- The power from the engine is diverted to the additional setup with the help of the valve, and then the hydraulic motor is used for the propulsion of the wheels.
- The hydraulic cylinders lift the additional setup whenever it is needed.

3.2 Assembling methodology

- The working of our project is a simple one that the assist of wheels along with the track of the excavator.
- Assemble the hydraulic system for the lifting of wheels in the chassis frame as like the supporting leg fittings in the back hoe loader.
- Take two dead axles, attach the hydraulic motor to the one of the dead axle
- Connect the hydraulic motor with the wheels for the movement.
- Connect the hydraulic motor with the main hydraulic tube which is responsible for the transmission of the track
- We connect our additional hydraulic line with the main line with the help of the valve.
- Attach the dead axles with the hydraulic lifting system.




Figure 1: *Proposed block diagram*

4. Results and Discussion

Subsequently the outcome is that the ordinary excavator is helped with the wheels so the excavator can have the option to go in both the lopsided landscape places and furthermore in the street surfaces with the assistance of the helped wheels. In the lopsided spots the extra wheels will be in the perfect position, if the excavator is expected to go in the street surfaces the extra wheels are lifted down with the assistance of the pressure driven chambers. At that point the three-way valve is utilized to redirect the pressure driven capacity to the extra wheel arrangement. The pressure driven force runs the water powered engine and afterward the water driven engine pushes the wheels.

4.1 Preparation of Figures and Tables

Real time excavator's working process




Figure 2: *Normal excavator working*



With the assist of the additional wheels




Figure 3: *Excavator assisted with wheels working*

5 Conclusions

Subsequently the outcome is that the ordinary excavator is helped with the wheels so the excavator can have the option to go in both the lopsided landscape places and furthermore in the street surfaces with the assistance of the helped wheels. In the lopsided spots the extra wheels will be in the perfect position, if the excavator is expected to go in the street surfaces the extra wheels are lifted down with the assistance of the pressure driven chambers. At that point the three-way valve is utilized to redirect the pressure driven capacity to the extra wheel arrangement. The pressure driven force runs the water powered engine and afterward the water driven engine pushes the wheels.

References

1. Betriebsvorschrift Schaufel rad bagger S, Year: 1974, "Those are very mind boggling electromechanical frameworks, of extraordinary mass, measurements and force, which are executing interpreter and slewing development".
2. B. Jevtović, Year: 1992, "Displaying and acknowledgment of sensors and actuators and neighborhood controllers of can wheel excavator SRs 1200 control framework", M.S. theory, Faculty of Electrical Engineering, University of Belgrade.
3. B. Jevtović; M. Mataušek Year: 2005, "A Predictive-Adaptive Hierarchical Control System of Bucket-Wheel Excavator: Theory and Experimental Results," Facta Universitatis, Ser.: Electronics and Energetics, Vol: 18, no: 3, pp. 493-503.



4. Bhaveshkumar P. Patel; Dr. J. M. Prajapati, Year: 2012, "Assessment of Bucket Capacity, Digging Force Calculations and Static Force Analysis of Mini Hydraulic Backhoe Excavator", Machine Design the Journal of Faculty of Technical Sciences, Serbia, Vol: 4, no: 4, pp. 1.
5. Daqing Zhang; Qinghua He; Peng Hao; HaiTao Zhang, Year: 2005, "Displaying and Controlling for Hydraulic Excavator's Arm", 22nd International Symposium on Automation and Robotics in Construction ISARC 2005, Ferrara (Italy), 2005, pp.1-7.
6. Demonstrating; Static Analysis of Backhoe Excavator Bucket (Mr.Swapnil S. Nishane 1, Dr. S.C. Kongre 2, Prof. K.A. Pakhare) (5)International Journal of Research in Advent Technology, Vol.4, No.3, March 2016 E-ISSN: 2321-9637 Available online at www.ijrat.org
7. W. Durst; W. Vogt, Year: 1988, "Bucket wheel excavator", Trans. Tech. Publications, Series of Mining Engineering, Vol: 7.