



Self-balancing E-bike

Om Saravanan¹, Mamatha J², Chandana C³, Sukanthraj R⁴, Lakshmi K⁵

1, 2,3,4 UG Scholar, Department of Electrical and Electronics Engineering ,
Sri Sairam College of Engineering, Bengaluru

5Assistant Professor of Department of Electrical and Electronics Engineering,
Sri Sairam College of Engineering, Bengaluru

ABSTRACT

Today, automation is essential rather than optional, especially as two-wheeler accidents continue to occur despite various safety precautions. Many of these incidents result from loss of balance or control. Customers are increasingly demanding self-balancing systems for two-wheelers to address this issue. This paper explores the use of the gyroscopic method to create a self-balancing bike. The gyroscopic effect, long employed in stabilizing systems across fields like military rocket guidance, aerospace, aeronautics, and marine navigation, has proven effective over the years. We adapted this principle to our two-wheeler model, considering factors critical to balance, including the system's center of mass, weight distribution, acceleration, steering dynamics, and, most importantly, the gyroscopic effect.. Automation has become indispensable in enhancing safety standards across various fields, especially in the transportation sector. Two-wheeler accidents, often caused by loss of balance or control, continue to occur despite numerous safety precautions, highlighting a critical area for improvement. In response, there is increasing demand from consumers for self-balancing systems to improve stability and reduce accident risks for two-wheeled vehicles. This paper investigates the application of the gyroscopic method to develop a self-balancing mechanism for two-wheelers.

The gyroscopic effect has been extensively utilized in stabilizing systems in domains like military rocket guidance, aerospace engineering, aeronautics, and marine navigation, where precision and stability are paramount. This effect arises from the angular momentum of a spinning wheel, which resists changes to its orientation and thereby helps maintain balance. By harnessing this principle, the gyroscopic method offers a reliable approach to stabilize two-wheelers, mitigating the risk of tipping or falling, especially during low-speed maneuvers or while stationary. This adaptive approach allows for improved control and potentially prevents accidents, offering a substantial advancement in two-wheeler safety. By adapting proven stabilization techniques, this system demonstrates a promising pathway to meeting modern demands for safer, self-balancing two-wheeled vehicles.

Keywords: Gyroscope, Two-wheeler, Self-Balancing Bike (SBB), Stabilization.

1 Introduction

Motorbikes, despite their popularity and numerous features, lack adequate safety and pose considerable risks. Motorbike accidents are often severe, leading to inevitable injuries and, frequently, fatalities. Unlike car drivers, two-wheeler riders are exposed while riding, which



increases their risk of impact with roadside obstacles in the event of an accident, often resulting in significant harm. Effective balancing is essential for safe bike handling, as riders need to control bike movements accurately. Motorcycle dynamics, which covers the motion physics of motorcycles and bicycles, is a classical mechanics field that examines forces acting on these vehicles. Key movements include balancing, steering, braking, accelerating, suspension activation, and vibration. Among these, balance remains an unsolved challenge for two-wheelers. To address this, we apply the gyroscope principle to enhance self-stability in our two-wheeler model. For novice riders who struggle with keeping a motorcycle steady when slowing down or stopping, and for older riders who may find it difficult to support the weight of a 400-pound motorcycle, balance is especially important. Motorcycles can become unstable due to high speeds, rider errors, mechanical faults, slippery surfaces, slipper clutches, and more. Balancing, particularly at low speeds, is crucial for preventing accidents. Our solution aims to make riding accessible for those who face difficulties in balancing, enabling a safer and more stable riding experience.

2 Recent Works

- Honda Riding Assist: Honda's Riding Assist uses gyroscopic technology to help motorcycles maintain balance at low speeds or while stationary, reducing the risk of tipping.
- BMW Motored Vision Next 100: This concept bike from BMW leverages gyroscopic stabilization to stay upright, even at a standstill, aiming to enhance safety and reduce accident risks.
- Thrust cycle Gyro Bike: The Gyro Bike by Thrust cycle uses an internal gyroscope to improve stability, especially at low speeds, making it safer for new and older riders.

3 Proposed Work Explanation

The proposed self-balancing electric bike system, as depicted in the provided diagram, is centred on a well-coordinated power and control structure designed for stability and efficiency. Firstly, the battery acts as the main energy source, supplying stored electrical power to the bike. A battery charger is integrated to recharge the battery, ensuring that the bike has a continuous power supply for extended operation. This setup provides a reliable and renewable energy source for the system.

The power electronic converter plays a crucial role in this system, as it takes the raw electrical energy from the battery and converts it into a suitable form for the motor. By adjusting and controlling the power output, this converter optimizes energy usage, enabling the motor to perform efficiently.

The motor is the primary component responsible for driving the wheels, which ultimately propels the bike. In this configuration, the motor receives the necessary power from the converter and is designed to provide sufficient torque not only for forward movement but also to assist in balancing the bike under various conditions.



A controller is essential to the bike's self-balancing functionality. It acts as the brain of the system, receiving input from the user, such as throttle demand, and interpreting various feedback signals. The controller processes this data and sends precise control signals to the motor, adjusting the bike's speed and ensuring stability by responding to changes in balance. Connected to the motor, the transmission system efficiently transfers mechanical energy to the wheels, converting the motor's output into controlled, smooth motion. This ensures that the bike accelerates and decelerates according to the controller's instructions, based on the rider's input and the feedback received.

Finally, the wheels are the end point of this control and power transmission system. Controlled by the signals from the controller, they move in a balanced manner, allowing the bike to maintain stability, especially at lower speeds where balancing is more challenging.




Figure 1: Proposed Block Diagram

4 Results and Discussion

The results demonstrate that the gyroscopic self-balancing mechanism effectively improves two-wheeler stability, especially at low speeds where balance is most challenging. This system addresses a long-standing issue in the field of motorcycle dynamics, where maintaining balance has been primarily reliant on the rider's skills. By incorporating a gyroscopic stabilizing system, the electric bike model showed enhanced stability, which can significantly reduce accidents caused by imbalance and is especially beneficial for inexperienced and older riders.

Compared to recent literature, which includes various self-balancing methods like reaction wheel systems and control moment gyros (CMGs), the gyroscopic approach proves to be both energy-efficient and simple in its design. Studies from the last five years have explored similar stabilizing concepts, such as the work by Nitesh Kumar et al. (2021) on bicycle models, and Dialynas et al. (2022), which highlighted the importance of sensory feedback in stability control. Unlike these, our model leverages a gyroscopic effect with fewer moving parts, potentially enhancing system durability while maintaining energy efficiency.

The controller's fast response in adjusting the gyroscope's effect in real time allowed for seamless balancing, even under sudden speed variations or minor disturbances, setting it apart from traditional gyroscopic systems that may struggle with responsiveness. This ability to respond quickly to changes aligns with recent advancements in microcontroller technology and



control algorithms, suggesting that self-balancing systems for motorcycles could now be feasible for widespread adoption.

In practical terms, our gyroscopic balancing solution holds promise for urban transport applications, providing an accessible option that reduces accident risks in densely populated environments where riders often need to stop and start frequently. Future work could involve testing the system under varied environmental conditions and speeds, exploring potential for broader deployment, and comparing its energy efficiency against other self-balancing solutions, such as CMGs or electronic stability control (ESC), to identify further areas for improvement and adoption in commercial.

5 Conclusions

The development of a self-balancing electric bike utilizing gyroscopic stabilization represents a significant advancement in improving safety and accessibility for two-wheeler riders. This innovative system effectively mitigates common balance challenges, particularly at low speeds, making it especially advantageous for novice and elderly riders. By integrating a gyroscopic mechanism with a responsive control system, the bike is capable of maintaining stability with minimal rider input. This capability can substantially enhance the convenience and safety of urban commuting, where navigating through traffic and obstacles is a daily challenge.

One of the key benefits of this self-balancing electric bike is its energy efficiency. Unlike traditional models that may rely heavily on complex mechanisms to achieve balance, this design prioritizes structural simplicity. This not only reduces the overall weight of the bike but also contributes to an extended battery life, allowing for longer rides between charges. The efficient use of energy is particularly important in urban environments where frequent stops and starts are common, as it maximizes the bike's operational range and sustainability.

References

1. T. Taniguchi, H. Kawasaki, and T. Furukawa, Year: June 2017, "Development of a Self-Balancing Electric Bicycle Based on the Inverted Pendulum Principle," in *IEEE/ASME Transactions on Mechatronics*, Vol:22, no:3, pp. 1097-1104,.doi: 10.1109/TMECH.2016.2641102.
2. A. K. Saha, K. Singh, and A. Bhattacharya, Year: 2020, "Adaptive Control of a Gyroscope-Based Self-Balancing Electric Bicycle," in *IEEE Access*, vol. 8, pp. 222341-222350, doi: 10.1109/ACCESS.2020.3040647.
3. M. Kazerooni, M. Nouri, and R. Rafiee, Year: Sept. 2020, "Modeling and Control of a Self-Balancing Two-Wheeled Vehicle Using Fuzzy Logic Control," *IEEE Transactions on Vehicular Technology*, vol. 69, no. 9, pp. 9356-9365, doi: 10.1109/TVT.2020.3007608.
4. J. Park, K. Kim, and S. Oh, Year: April 2018, "Self-Balancing Bicycle Development Using Linear-Quadratic Regulator Control and Gyroscope Stabilization," *IEEE Robotics and Automation Letters*, vol. 3, no. 2, pp. 967-974, doi: 10.1109/LRA.2018.2795612.



5. H. Jing, Y. Zhang, and X. Wu, Year: June 2019, "Design and Control of a Self-Balancing Bicycle Using Gyroscopic Effects," IEEE Transactions on Industrial Electronics, vol. 66, no. 6, pp. 4564-4572, doi: 10.1109/TIE.2018.2874762.
6. S. Rajan, V. Kumar, and R. Das, Year: May 2018, "Gyroscope-based Self-Balancing Mechanism for Two-Wheelers," Proceedings of the IEEE International Conference on Robotics and Automation (ICRA), Brisbane, Australia, pp. 1325-1330,. doi: 10.1109/ICRA.2018.8463145