



Article Title: Finger Vein Detection Using Deep Learning Method: A Review

Finger Vein Detection Using Deep Learning Method: A Review

Balamurugan M¹, Sukanya S T²

¹Department of MCA, Narayanaguru College of Engineering, Anna University, Chennai.

² Assistant Professor, Department of MCA, Narayanaguru College of Engineering, Anna University.

ABSTRACT

Nowadays, high security is the most essential requirement for spoofing attacks. There is more demand for more security and more precision and more speed of authentication for buying electronics. There is a large scope solution for security issues is human observable and physiology characteristic in bioscript. In any case, in phrases of both time and space the biometric systems are highly complex, for high security this is not that much appropriate. Consequently, for high authentication, in this paper investigating various methods used in the existing work for the finger vein recognition system.

Keywords: Deep Learning, Convolution Neural Network, Biometric System, Finger Vein Recognition, Recognition System.

1 Introduction

The quick advancement Mission vision application became broader and inside and out by using biometric identification technology. In the meantime, here, there are more and more identity authentication security by improvement of innovation and modern science. Among them, Because of living identification and high anti counter fitting. Data security, network instalment and in different fields in this innovation of finger vein recognition is applied. Establish finger-vein recognition on the edges of dominance has stood out for additional specialists. Finger-vein distinguishing proof frameworks as a rule comprise of two cycles, specifically, highlight extraction and coordinating. Finger veins comprise a lot of abnormal quality information, Parts were hidden, and there was a lot of noise. Similar data can be found in finger-vein images of a similar finger, however there are some differences. a large distinction among diverse fingers. Consequently, individuals normally select practical examples from their finger veins and coordinate methodologies for recognition. Most finger-vein recognition frameworks principally contain two modes: verification and recognition. Normally, the models are separated by 2(two) sorts: Those are non-learning models and learning models. Gabor channels in non-learning models are considered as a compelling extractor of the vein line. Zhou and Kumar hired a reasonable mixture of morphological activities or even Gabor channels to accomplish shape highlights.

Line Local Binary Patterns are utilized by a few different researchers to extract parallel vein surface highlights, whereas Scale Invariant Feature Transformation is employed to extract the functions of specific locations. The Hamming distance and the Euclidean distance are the most



Article Title: Finger Vein Detection Using Deep Learning Method: A Review

popular matching strategies for transforming functions into vectors and improving recognition strength. Yang et al. Relative commons attribution 4.0 license those work is under this. Recognition is examined the life systems structure and for execution improvement vein extraction joined with the coordination matching technique. However, for the serious effect of certain issues the above algorithm is defence less, for example: quality of Low intensity, low picture, and non-finger place intern vein-surface block loss. In this manner, individuals have slowly presented some learning calculations, which appreciate sturdy adaptability and aren't inclined to the environment.




Figure 1: Block Diagram of Finger Vein Recognition Techniques

Gabor channels proposed to delete highlights Finger veins and Support Vector Machines were used to classify the data. For the classification matching they acquire the fundamental data and neural network from Principal Component Analysis (PCA). In learning models, for non-finger area end, noisy data preparation, and other applications preparation extraction of Region of Interest is fundamental stage. Further developed the form finger vein the extraction of ROI in knuckle area. The component features had been modified into particle capabilities after the upgrade, for recognition they utilized the layered hypersphere technique.

1.1 Class Generalization and DGLV Construction

In practice, the crucial element that influences the recognition precision is unseen categories with new examples. The conventional passive exam in finger-vein frameworks will cause actual reputation interference, while recognizing unseen examples that both bad recognition and low recognition efficiency affects, can manage the conformation of recent finger veins,




Article Title: Finger Vein Detection Using Deep Learning Method: A Review

however absence of training and plenty of time utilization. It is important to choose the essential correlation tests and time usage of M examinations in the recognition mode. Our version now no longer has the most effective accuracy and time intake in addition to generalization ability. In view of very separate roles and speculation, DHLFV has acquired a less blunder rate, representing 1.481% and 2.228%. The FV-SIPL database conducted extra experiments to verify further effectiveness. Compared to a greater part of most recent finger vein recognition models the experimental results achieved better, with significant application value.

1.2 Finger Vein Recognition Without Using the Blur Restoration

By changing the picture using micro focuses removed from the finger-vein region, Lee et al., developed a method for recognising finger veins. Using a binary pattern that is locally to separate finger-vein highlights and the extricated highlights to calculate the Hamming distance. Peng et al., used eight-direction Gabor channels on the first finger-vein picture and used the combination of the picture and the vein design to separate the finger-vein design. They suggested a scale- invariant model. However, when it comes to finger vein photos of varying quality, this technique can degrade the channel's execution, and since this test was conducted in a limited environment, it can be powerful to picture variations, like enlightenment or misalignment. In addition, they didn't consider the haze that could happen while catching a finger vein picture.





Article Title: Finger Vein Detection Using Deep Learning Method: A Review




Figure 2: Finger Vein Detection

2 Related Works

2.1 [1]. Finger-Vein Verification Using Gabor Filter and SIFT Feature Matching.

In 2012, Peng, N. Wang, A. A. A. El-Latif, Q. Li, and X. Ni, demonstrated a novel method to verify the infrared finger-vein patterns proposed for biometric purposes. Firstly, we select parameters for Gabor filter with eight orientations to exploit the finger-vein network, then we extract vein patterns by the fusion of two distinct orientation results. Secondly, we utilize SIFT features to offset the effect of image rotation and shift impact during finger-vein verification. Finally, the number of matching SIFT features between the registered and test finger vein patterns is calculated as the similarity measurement to verify the personal identification. The experiment results show that EER is low to 0.46%, which demonstrates our proposed approach is valid and effective for finger-vein verification.

2.2 [2]. Human Identification Using Finger Images, IEEE Transaction.

In 2012, A. Kumar and Y. Zhou, demonstrated a new approach to improve the performance of finger-vein identification systems presented in the literature. The proposed system simultaneously acquires the finger-vein and low-resolution fingerprint images and combines these two evidences using a novel score-level combination strategy. We examine the previously proposed finger-vein identification approaches and develop a new approach that illustrates its superiority over prior published efforts. The utility of low-resolution fingerprint images acquired from a webcam is examined to ascertain the matching performance from such images. We develop and investigate two new score-level combinations, i.e., holistic and nonlinear fusion, and comparatively evaluate them with more popular score-level fusion approaches to ascertain their effectiveness in the proposed system. The rigorous experimental results



Article Title: Finger Vein Detection Using Deep Learning Method: A Review

presented on the database of 6264 images from 156 subjects illustrate significant improvement in the performance, i.e., both from the authentication and recognition experiments.

2.3 [3]. Finger-Vein Verification Based On Multi-Features Fusion

In 2013, Qin, L. Qin, L. Xue, X. He, C. Yu, and X. Liang, demonstrated a new scheme to improve the performance of finger-vein identification systems. Firstly, a vein pattern extraction method to extract the finger-vein shape and orientation features is proposed. Secondly, to accommodate the potential local and global variations at the same time, a region-based matching scheme is investigated by employing the Scale Invariant Feature Transform (SIFT) matching method. Finally, the finger-vein shape, orientation and SIFT features are combined to further enhance the performance. The experimental results on databases of 426 and 170 fingers demonstrate the consistent superiority of the proposed approach.

2.4 [4]. Identification of Finger Vein Using Neural Network Recognition Research Based On PCA

In 2017, He, Z. Li, L. Chen, and J. Peng, demonstrated on Finger vein identification, as an important part in biological feature identification, has been widely used in various fields. The finger vein image shows the vein structure captured under infrared ray. This paper firstly adopts the principal component analysis (PCA) to extract low-dimension features of vein images; and then constructs a multi-layer neural network classifier based on BP Neural Network, to realize the identity recognition. Experiments show that the proposed method reaches a satisfactory accuracy of 81% in recognizing 600 images, showing a great value in application.

2.5 [5]. Convolutional Neural Network-Based Finger-Vein Recognition Using NIR Image Sensor

In 2017, Hong, M. Lee, and K. Park, demonstrated that, Conventional finger-vein recognition systems perform recognition based on the finger-vein lines extracted from the input images or image enhancement, and texture feature extraction from the finger-vein images. In these cases, however, the inaccurate detection of finger-vein lines lowers the recognition accuracy. In the case of texture feature extraction, the developer must experimentally decide on a form of the optimal filter for extraction considering the characteristics of the image database. To address this problem, this research proposes a finger-vein recognition method that is robust to various database types and environmental changes based on the convolutional neural network (CNN). In the experiments using the two finger-vein databases constructed in this research and the SDUMLA-HMT finger-vein database, which is an open database, the method proposed in this research showed a better performance compared to the conventional methods.



2.6 [6]. Finger Vein Recognition with Anatomy Structure Analysis

In 2018, Yang, G. Yang, Y. Yin, and X. Xi, demonstrated that, Finger vein recognition has received a lot of attention recently and is viewed as a promising biometric trait. In related methods, vein pattern-based methods explore intrinsic finger vein recognition, but their performance remains unsatisfactory owing to defective vein networks and weak matching. One important reason may be the neglect of deep analysis of the vein anatomy structure. By comprehensively exploring the anatomy structure and imaging characteristic of vein patterns, this paper proposes a novel finger vein recognition framework, including an anatomy structure analysis-based vein extraction algorithm and an integration matching strategy. Specifically, the vein pattern is extracted from the orientation map-guided curvature based on the valley- or half valley-shaped cross-sectional profile. In addition, the extracted vein pattern is further thinned and refined to obtain a reliable vein network. In addition to the vein network, the relatively clear vein branches in the image are mined from the vein pattern, referred to as the vein backbone. In matching, the vein backbone is used in vein network calibration to overcome finger displacements. The similarity of two calibrated vein networks is measured by the proposed elastic matching and further recomputed by integrating the overlap degree of corresponding vein backbones. Extensive experiments on two public finger vein databases verify the effectiveness of the proposed framework.

3 Conclusion

In this paper, the different strategies for the recognizing finger veins is studied. It is obvious that the CNN example is preferable to classical computations. CNN is also a full system with a lot of power and is easy to use for finger vein recognition. In light of CNN's dominant exhibition, will perform additional study using deep learning approaches on finger vein recognition. An important component of finger vein recognition is the capacity to create a public data set with a vast amount of information.

References

1. Kumar Ajay; Yingbo Zhou, Year: 2012, "Human identification using finger images," IEEE Transaction on Image Processing, Vol: 21, no: 4, pp. 2228–2244.
2. Qin Huafeng; Lan Qin; Lian Xue; Xiping He; Chengbo Yu; Xinyuan Liang, Year: 2013, "Finger-vein verification based on multi-features fusion," Sensors, Vol: 13, no: 11, pp. 15048–15067.
3. Hong Hyung Gil; Min Beom Lee; Kang Ryoung Park, Year: 2017, "Convolutional neural network-based finger-vein recognition using NIR image sensors," Sensors, Vol: 17, no: 6, pp. 1297-1301.
4. Yang Lu; Gongping Yang; Yilong Yin; Xiaoming Xi, Year: 2018, "Finger vein recognition with anatomy structure analysis," IEEE Transaction on Circuits System and Video Technology, Vol: 28, no: 8, pp. 1892–1905.



Article Title: Finger Vein Detection Using Deep Learning Method: A Review

5. Srinivas, K. N; R. Arumugam, Year: 2002, "Finite element analysis combined circuit simulation of dynamic performances of switched reluctance motors," *Electronic Power Component System*, Vol: 30, no: 10, pp. 1033–1045.
6. Rosdi Bakhtiar Affendi; Chai Wuh Shing; Shahrel Azmin Suandi, Year: 2011, "Finger vein recognition using local line binary pattern," *Sensors*, Vol: 11, no: 12, pp. 11357–11371.
7. Yang Jinfeng; Jianze Wei; Yihua Shi, Year: 2019, "Accurate ROI localization and hierarchical hyper-sphere model for finger-vein recognition," *Neurocomputing*, Vol: 328, no: 5, pp. 171– 181.
8. Zhou Yingbo; Ajay Kumar, Year: 2011, "A. Human identification using palm-vein images", *IEEE Transaction on Forensics Security*, Vol: 10, no: 2, pp. 1259–1274.
9. Lee Eui Chul, Kang Ryoung Park, Year: 2009, "Restoration method of skin scattering blurred vein image for finger vein recognition," *Electronics Letters*, Vol: 45, no: 21, pp. 138-142.
10. Song Wonseok; Kim Taejeong; Kim Hee Chan, Year: 2011, "A finger-vein verification system using mean curvature," *Pattern Recognition Letters*, Vol: 32, no: 11, pp. 1541-1547.
11. Wang Lingyu; Graham Leedham, David Siu-Yeung Cho, Year: 2008 "Minutiae feature analysis for infrared hand vein pattern biometrics," *Pattern Recognition*, Vol: 41, no: 6, pp. 920-929.
12. P. Kallo; I. Kiss; A. Podmaniczky; J. Talosi, Year: 2001, "Detector for recognizing the liveness character of a finger in fingerprint recognizing apparatus," *Electronics Letters*, Vol. 56, no: 7, pp. 1284-1289.
13. Yang Lu; Gongping Yang; Yilong Yin; Xiaoming Xi, Year: 2018, "Finger vein recognition with anatomy process," *IEEE Transaction on Circuits System and Video Technology*, Vol: 38, no: 8, pp. 1792–1895.
14. Srinivas, K. N; R. Arumugam, Year: 2002, "Finite element analysis combined circuit simulation of dynamic performances of switched reluctance motors," *Electronic Power Component System*, Vol: 30, no: 10, pp. 1033–1045.
15. Rosdi Bakhtiar Affendi; Chai Wuh Shing; Shahrel Azmin Suandi, Year: 2011, "Finger vein recognition using local line binary pattern," *Sensors*, Vol: 11, no: 12, pp. 11357–11371.
16. Yang Jinfeng; Jianze Wei; Yihua Shi, Year: 2019, "Accurate ROI localization and hierarchical hyper-sphere model for finger-vein recognition," *Neurocomputing*, Vol: 328, no: 5, pp. 171– 181.