



Article Title: **Review on Spray Coating Techniques**

Review on Spray Coating Techniques

K.R. Harish¹, Dr. M. Edwin Sahayaraj², Dr. B. Stanly Jones Retnam³

¹Research Scholar, Department of Mechanical Engineering, Noorul Islam Centre for Higher Education, Kumaracoil, Tamil Nadu, India. E-Mail: harishrajamoni@gmail.com

²Associate Professor, Department of Automobile Engineering, Noorul Islam Centre for Higher Education, Kumaracoil, Tamil Nadu, India. E-Mail: edwinsahayaraj@niuniv.com

³Associate Professor, Department of Automobile Engineering, Noorul Islam Centre for Higher Education, Kumaracoil, Tamil Nadu, India. E-Mail: bsjsjr@gmail.com

ABSTRACT

A vast array of plating processes, the substances through which different plating can be applied with the natural intention of saving the component, shape and the outer layer that are left unprotected to any kind of physical, chemical and also mechanical adversities. Thus, Spray pyrolysis is very efficient, cost effective, and utilizes simple equipment. Spray pyrolysis is an important technique in which a thin film is deposited on the dielectric matrix by spraying a precursor solution on a heated surface. Spray pyrolysis has been applied to deposit a wide variety of thin films. These films were used in various devices such as solar cells, carbon solar cells, sensors, and solid oxide fuel cells, etc. It is observed that often the properties of deposited thin films depend on the preparation conditions. An extensive investigation of the effects of spray parameters on film quality is given to demonstrate the importance of the process of optimization. However, spray pyrolysis seems not useful due to poor quality of thin film, thermal decomposition, and vapor convection. The vapors are generated due to temperature difference, which restricts the source from binding with the substrate. In this paper, briefly study the spray pyrolysis techniques and using the same for metal coating done over polymers. Also, this study highlighted many research obstacles and presented future direction for research in developing new methodology using the inadequacies of the existing approaches.

Keywords: coating, polymers, spray pyrolysis, thin films, wear.

1 Introduction

Each and every scrap in the field of mechanical are manufactured in unique way and has its own specifications. For particular purposes, mechanical structures and parts are created. These pieces must first be fabricated while adhering to stringent material selection requirements. Body materials, mechanical characteristics, desired functionality, characteristics of thermal, conducting capacity of electrical appliances, resistance against corrosion which include creep, torsion, tension, compression, friction, transferring capability of the heat flux, vibrating feature, rotating with high speed are some of these restrictions.

In addition, additional factors including material availability, cost, safety, and toxicity must be taken into account. The latter group is crucial in completing the material selection procedures



Article Title: Review on Spray Coating Techniques

before producing the scrap and the architectural design of any scrap in this field. Consider the following example, the silverware has the highest electric conductivity value, even though it is too expensive to fabricate in a large quantity [1].

For the process of establishing the fresh actuators, the shape memory effect and super elasticity are used with the help of the characteristics of the NiTi amalgam. The shape memory effect and the super elasticity are combined together to manufacture creative equipment for the purpose of performing the minute operations within the body of the human, these alloys also offer exceptional biocompatibility. Unfortunately, Ni ions, a poisonous and damaging class of elements for living organs, are released as a consequence of NiTi emitting its corrosion. [2] The heat and the electricity conducting capacity is extremely high in copper with various features. In spite of it the copper undergoes very less rigidity. When the copper is put under the pressure of rotary cooling fin, the rigidity reduces because of the extreme susceptibility of copper [3].

There have been unique approaches proposed, including thermal, amalgam procedures, plating to address issues and embellish fabric homes for specific applications. Coating techniques, out of all of these options, have the best aspect of fabric improvement since coating layers can restrict the price and forget about material shortages because their thickness barely ever exceeds a few micrometres. While there are many different safety techniques including thermal, mechanic, finishing with chemical, polishing which are not included in this review, it does cover common coating procedures, materials, and associated floor change excellent. In this section the process of spray pyrolysis and the mechanism followed are explained clearly. The problems faced while performing this process is also explained.

2 Literature Review

Anwaar et al. [1] looked into the impact of a full plasma flow charge on the interaction of plasma feedstock with the inside of the nozzle through plasma torch and the accompanying the depositing method in 2018. Theoretical calculations show that the least flowing capacity of plasma is said to be eighty-five liters per minute, major electricity eleven thousand two hundred and seventy-six per kilogram has been transmitted into the powder feedstock which is injected into it. The enthalpy transported and dropped sequentially with the rise of overall drift rate. It increases by eighty-five litre per minute to hundred litre per minute. Furthermore, decrease in electricity is caused by a decrease in temperature and an increase in momentum from the feedstock fabric combined accompanied by a larger total plasma flow. 7~8. The coating microstructures were created using weight percent agglomerated YSZ powder.

By analysing even, the smallest structure, segment which includes composite, grain distributor and also the columnar crystal inclination of 7YSZ plating made with PS-PVD in 2021, Yin et al. [2] addressed following morphology of 7YSZ TBCs. The results show that an apparent intended inclination with all through the whole coated place with cross section is revealed by growth about YSZ columnar crystals. Tetragonal section makes up 65.8% of



Article Title: Review on Spray Coating Techniques

the coating's composition, and it has a significant preference for boom behaviour. The analysis of nano-indentation indicates that from bottom to top, the coating's micro hardness will gradually grow. Also, based entirely with the results of velocity, temperature condition in their numerical value along with the stress present inside the plasma jet, the located characteristics of the 7YSZ particle are analysed.

In 2020, Zhang et al. [3] looked at the process by which vertical cracks develop during PS-PVD as well as the results how thick it is coated along with the substrate temperature. Moreover, optical spectroscopy has been used to further evaluate reciprocation between spray powder and plasma flame while deposition of coating process is carried out. According to the evidence, Yb₂SiO₅ and mullite coating's different thermal development rates, the brief cooling that occurs later along with deposition and nucleation in Yb₂SiO₅ that has vaporized all contribute to form vertical fissures.

2019 saw the investigation of the connections along with the parameters of the spray and the micro structure by Zhao et al [4]. It was discovered that comparing to spray distance the carrier gas and net power have a greater impact on the microstructure in the process of overlaying. In order to examine the chemical composition of the coatings and also the composition of coating in phase the energy dispersive spectroscopy and X ray diffraction are used sequentially. The findings show a positive association of the standard atomic ratio between the La and Ce during the process of layering with the characteristics of lattice of LC phases. Transmission electron microscope was used to examine the geographical properties of the improved coating (TEM). The coating is pyrochlore phase, as demonstrated by TEM super-lattice diffraction patterns.

According to a specified experimental plan, Deng et al. [5] created 7YSZ coating in 2019 via plasma spraying physical vapour deposition (PS-PVD). In-depth research was done between the minute structures along with the deposit characteristics in the 7YSZ coating. Findings indicate that the coating exhibits radial regional characteristics that can be classified by 3 general categories namely, In Category I, coating is entirely made structures in a columnar way which represents the cauliflower shape, with the properties of rough surface having the stability in deposit efficiency; in category III, the coating is done by mixing the solid particles along with the droplets and the gas by not implementing any columnar way; in category II, intersects both the Zones I and III, consisting columns along with a columnar way which leads to the structure in a dome shape.

Based on the review of these selected paper is formed in the form of table and is given below. The table 1 clearly explains the literature survey of a few selected paper in which the review is taken and the advantages, disadvantages, year in which the paper is published, the authors of the particular paper, material used in that process is also mentioned along with the performance performed is also recorded noted and listed down in the following table. All the details are clearly mentioned in the table clearly. Various paper are taken for the reviewing process and examined clearly. The materials they have used and the performance performed by the material



Article Title: Review on Spray Coating Techniques

at certain degree are also recorded and clearly mentioned and are discussed in this section clearly. In this section few papers are explained briefly the method, material and performance by them along with their heating as well as the cooling temperature with their reaction.

3 Conclusion

There are a number of influencing factors, such as material that deposit, material that substrate, form of the feedstock, and deposition processes, that must be considered for successfully depositing the substrate during the coating process. The most crucial processes, however, involve deposition because they deal with the chemistry of materials and the alloying of compositional elements in the coating layer. One can choose the method in which the deposition can take place by considering the various characteristics. Physical/chemical vapour deposition (PVD/CVD), sol-gel, and other thermal spraying procedures are found to be the accurate method for deposition. Material selection is crucial to achieving the best coating efficiency because the procedures indicated use various method for depositing particular material type on surfaces. Several processes are used to convert the feed stocked liquid to semi solid which takes the form of clusters, droplets and particles using thermal sources. Further substances deposit the stuff in the absence of any change in the chemical state with differences in electrochemical charges between the poles. Materials, the method in which deposit has occurred also affects the process of coating layers.

Reference

1. A. Anwaar; L. Wei; B. Zhang; H. Guo, Year: 2018 "Plasma flow optimization for 7YSZ quasi-columnar coating by plasma spray-physical vapor deposition", IEEE, pp: 5-11.
2. Juhang Yin; Cheng Lai; Xiaofeng Zhang; Li Zhang, Xu Wang; Xin Wang; Ziqian Deng; Xueshi Zhuo, Bing He; Longjiang Deng, Year: 2021, "Microstructural and columnar growth characteristics of 7YSZ thermal barrier coatings fabricated by plasma spray physical vapor deposition" , Journal of the European Ceramic Society.
3. Xiaofeng Zhang; Chao Wang; Ruijun Ye; Chunming Deng; Xinghua Liang; Ziqian Deng; Shaopeng Niu; Jinbing Song; Guo Liu; Min Liu; Kesong Zhou; Jian Lu; Junli Feng, Year: 2020, "Mechanism of vertical crack formation in Yb₂SiO₅ coatings deposited via plasma spray- physical vapor deposition", Journal of Materiomics, Vol: 6.
4. Cong Zhao; Wenting He; Liangliang Wei; Hongbo Guo, Year: 2019, "Microstructures of La₂Ce₂O₇ coatings produced by plasma spray-physical vapor deposition", Journal of the European Ceramic Society.



Article Title: Review on Spray Coating Techniques

5. Qian Deng; Jie Mao; Min Liu; Chun-Ming Deng; Jing-Tao Ma, Year: 2019, "Regional characteristic of 7YSZ coatings prepared by plasma spray-physical vapor deposition technique", Rare metals.
6. R. Kamal Jayaraj; S. Malarvizhi; V. Balasubramanian, Year: 2018, "Optimizing the micro-arc oxidation (MAO) parameters to attain coatings with minimum porosity and maximum hardness on the friction stir welded AA6061 aluminium alloy welds", Defence Technology.
7. A. Simimol; S. Prasanna Kumar; Shivnath Kumar; Manik Kumar Das; A. Lalu Alex, SaketKhandekar; U. Shanmuganathan; and Meduri Ravi, Year: 2019, "Electrodeposition of Cesium for Efficient Explosive Emission Carbon Fiber Cathodes", IEEE Transactions On Plasma Science, Vol: 47, no: 8.
8. SabarisonPandiyarajana; Zhao Chen Liu; Ai-HoLiaoc; MuthusankarGanesanb; Sheng-Tung Huang; Chen-Ta Lee; Ho-Chiao Chuang, Year: 2021, "High-performance anti-corrosion behavior of graphene oxide decorated nickel coating by novel ultrasonic-assisted supercritical-CO₂ electrode position approach", ElectrochimicaActa, Vol: 387.
9. Mohammed N. Khan; Sohail Shah; Tariq Shamim, Year: 2020, "Investigation of operating parameters on high-velocity oxyfuel thermal spray coating quality for aerospace applications", The International Journal of Advanced Manufacturing Technology.
10. Haihua Yao; Zheng Zhou; YunfeiXue; Zhenlu Zhou; Zhen Tan; Dingyong He; Benpeng Wang; Lu Wang, Year: 2019, "Microstructure and thermal conductivity of wire-arc sprayed FeCrNbBSiC amorphous coating", Journal of Alloys and Compounds, Vol: 788.
6. R. Kamal Jayaraj; S. Malarvizhi; V. Balasubramanian, Year: 2018, "Optimizing the micro-arc oxidation (MAO) parameters to attain coatings with minimum porosity and maximum hardness on the friction stir welded AA6061 aluminium alloy welds", Defence Technology.
7. A. Simimol; S. Prasanna Kumar; Shivnath Kumar; Manik Kumar Das; A. Lalu Alex, SaketKhandekar; U. Shanmuganathan; and Meduri Ravi, Year: 2019, "Electrodeposition of Cesium for Efficient Explosive Emission Carbon Fiber Cathodes", IEEE Transactions On Plasma Science, Vol: 47, no: 8.
8. SabarisonPandiyarajana; Zhao Chen Liu; Ai-HoLiaoc; MuthusankarGanesanb; Sheng-Tung Huang; Chen-Ta Lee; Ho-Chiao Chuang, Year: 2021, "High-performance anti-corrosion behavior of graphene oxide decorated nickel coating by novel ultrasonic-assisted supercritical-CO₂ electrodeposition approach", ElectrochimicaActa, Vol: 387.



Article Title: Review on Spray Coating Techniques

9. Mohammed N. Khan; Sohail Shah; Tariq Shamim, Year: 2020, "Investigation of operating parameters on high-velocity oxyfuel thermal spray coating quality for aerospace applications", The International Journal of Advanced Manufacturing Technology.
10. Haihua Yao; Zheng Zhou; YunfeiXue; Zhenlu Zhou; Zhen Tan; Dingyong He; Benpeng Wang; Lu Wang, Year: 2019, "Microstructure and thermal conductivity of wire-arc sprayed FeCrNbBSiC amorphous coating", Journal of Alloys and Compounds, Vol: 788.
10. Haihua Yao; Zheng Zhou; YunfeiXue; Zhenlu Zhou; Zhen Tan; Dingyong He; Benpeng Wang; Lu Wang, Year: 2019, "Microstructure and thermal conductivity of wire-arc sprayed FeCrNbBSiC amorphous coating", Journal of Alloys and Compounds, Vol: 788.